



NEUTRIK XLR PANEL CONNECTORS: D-L series

Universal metal-bodied housing common to most Neutrik connector ranges allows simpler metalworking and more flexibility of use. Panel cutout 24mm, connector can be mounted front or rear of panel. Available in 3, 4, 5, 6 and 7-pin configurations. Metal body offers RF protection. The NC3FD-L-0 is a latchless version of the NC3FD-L.

Standard connectors have countersunk clearance mounting holes to accept M3 bolts. The special 'M3' version of the connector has an M3 tapped thread, for speed of mounting. This obviously means that they can only be used rear-of-panel mounted.

B suffix = black shell, gold plated contacts, BAG = black shell with silver plated contacts.

40-397	NEUTRIK XLR NC3FD-L-1 Female panel
40-398	NEUTRIK XLR NC3MD-L-1 Male panel
40-393	NEUTRIK XLR NC3FDM3-L-1 Female panel
40-394	NEUTRIK XLR NC3MDM3-L-1 Male panel
40-399	NEUTRIK XLR NC3FD-L-0-1 Female panel (no latch)
40-497	NEUTRIK XLR NC4FD-L-1 Female panel
40-498	NEUTRIK XLR NC4MD-L-1 Male panel
40-493	NEUTRIK XLR NC4FDM3-L-1 Female panel
40-494	NEUTRIK XLR NC4MDM3-L-1 Male panel
40-597	NEUTRIK XLR NC5FD-L-1 Female panel
40-598	NEUTRIK XLR NC5MD-L-1 Male panel
40-593	NEUTRIK XLR NC5FDM3-L-1 Female panel
40-594	NEUTRIK XLR NC5MDM3-L-1 Male panel
40-697	NEUTRIK XLR NC6FD-L-1 Female panel
40-698	NEUTRIK XLR NC6MD-L-1 Male panel
40-694	NEUTRIK XLR NC6MDM3-L-1 Male panel
40-797	NEUTRIK XLR NC7FD-L-1 Female panel
40-798	NEUTRIK XLR NC7MD-L-1 Male panel
41-395	NEUTRIK XLR NC3FD-L-BAG-1 Female panel
41-396	NEUTRIK XLR NC3MD-L-BAG-1 Male panel
41-397	NEUTRIK XLR NC3FD-L-B-1 Female panel
41-398	NEUTRIK XLR NC3MD-L-B-1 Male panel
41-497	NEUTRIK XLR NC4FD-L-B-1 Female panel
41-498	NEUTRIK XLR NC4MD-L-B-1 Male panel
41-597	NEUTRIK XLR NC5FD-L-B-1 Female panel
41-598	NEUTRIK XLR NC5MD-L-B-1 Male panel
41-697	NEUTRIK XLR NC6FD-L-B-1 Female panel
41-698	NEUTRIK XLR NC6MD-L-B-1 Male panel
41-797	NEUTRIK XLR NC7FD-L-B-1 Female panel
41-798	NEUTRIK XLR NC7MD-L-B-1 Male panel

UK Sales - tel 0191 418 1122
 fax 0191 418 1123
 sales@canford.co.uk

International Sales - tel +44 191 418 1133
 fax +44 191 418 1134
 international@canford.co.uk

Tech Support - tel 0191 418 1144
 fax 0191 418 1145
 techsupport@canford.co.uk