



CANFORD ELECTRET MICROPHONE ADAPTERS

Lapel microphones used with radio-mic transmitter body-packs usually require a low-voltage bias that is normally provided by the pack. These useful adapters take the place of the pack, plugging directly into a standard XLR-3 microphone connection. The adapter derives a power supply for the microphone from a mixer or standard phantom power supply, and provides a balanced output.

Several versions are available for commonly-encountered microphones, together with a test-bench "bodge" version, providing spring-terminals for testing unterminated microphones. The bodge version may also be useful for live emergency situations such as unforeseen flat batteries in a transmitter pack.

Please note that the connectorised versions, other than the 20-767 are for use with 2-wire microphones.

Versions available

Stock code	Microphone connector	Compatible with
20-761	Spring terminals	Test work (max. wire diameter 1.8mm)
20-762	Hirose (HRS) 4-pin	Canford, Audio Technica
20-763	4-pin Lemo	Trantec, Beyer
20-764	8-pin Hermaphrodite Lemo	Micron (2-wire)
20-765	4-pin Tiny QG	Shure, Audio-Technica
20-767	8-pin Hermaphrodite Lemo	Micron (3-wire)
20-768	3-pin Lemo	Sennheiser 3000 and 5000 series
20-769	3.5mm locking jack	Sennheiser Evolution G1/G2 series

Technical Specification:

Phantom power:	24-48V
Insertion loss:	3 to 8 dB, depending on microphone
Audio output:	Balanced, male XLR
Dimensions:	19mm (diameter) x 105mm

Manufactured by Canford.

20-761	CANFORD ELECTRET MICROPHONE ADAPTER Bodge
20-762	CANFORD ELECTRET MICROPHONE ADAPTER HRS
20-763	CANFORD ELECTRET MICROPHONE ADAPTER Lemo 4-pin
20-764	CANFORD ELECTRET MICROPHONE ADAPTER Lemo 8-pin
20-765	CANFORD ELECTRET MICROPHONE ADAPTER Tiny QG
20-767	CANFORD ELECTRET MICROPHONE ADAPTER Lemo 8-pin 3-wire
20-768	CANFORD ELECTRET MICROPHONE ADAPTER Lemo 3-pin
20-769	CANFORD ELECTRET MICROPHONE ADAPTER 3.5mm jack

UK Sales - tel 0191 418 1122
 fax 0191 418 1123
 sales@canford.co.uk

International Sales - tel +44 191 418 1133
 fax +44 191 418 1134
 international@canford.co.uk

Tech Support - tel 0191 418 1144
 fax 0191 418 1145
 techsupport@canford.co.uk