


CM6T

6.5" two-way loudspeaker



Apart CM6T is a two-way low impedance or 100 volt loudspeaker suitable for the distribution of microphone calls and background music. In 16 ohms use, you can connect up to 4 loudspeakers in parallel on each channel of a standard 4 ohms amplifier.

For 100 volt use, the CM6T is equipped with a high-quality 6 watt 100 volt transformer with several power tapings (6 - 3 - 1.5 watts).

CM6T is easy to install, due to its simple quick mounting system with only 3 screws.

From 12 pieces on, the CM6T loudspeakers can be painted optionally in any other RAL color (Ref. PAINT-CM).

The housing is made of high quality ABS. The 6 ½" woofer is made of special enforced polypropylene what results in a very low distortion. To complete the sound, a quality 1" tweeter has been integrated. The grille is made of aluminium what makes CM6T humidity proof and suited for bathrooms, kitchens...

TECHNICAL SPECIFICATIONS

outside diameter in mm	205	depth in mm	75
cutout in mm	186	loudspeaker system	2-way
woofer size in inch	6,5	woofer cone material	polypropylene
tweeter size	1 inch	mounting system	3 screws
colour	white	100V transformer power taps in watts	6 - 3 - 1.5
impedance in ohms	16	low impedance dynamic power in watts	60
SPL 1W/1m in dB	87	max SPL 1m in dB	105
frequency response in Hz	60 - 20K	main construction material	ABS plastic
grille main material	aluminium	IP rating	54
applicable low impedance	Yes	applicable in 100V	Yes
Vertical dispersion angle 1000 Hz	180°		

[MORE PICTURES](#)



ACCESSORIES



CMBB

On-Wall box for CM loudspeaker range