



ASSEMBLY RECOMMENDATION

speakON® | Chassis mounting

Fastening recommendation for Neutrik speakON chassis connectors

■ Rear mounted connectors:

- Fast and convenient mounting with **Neutrik A-Screw** self-tapping Plastite® screws: "-2" or "-3" suffix versions (examples: **NL4MDXX-V-2**, **NL4MDXX-V-3**)
- Speed-optimized mounting with countersunk holes and optional **MFD** rear mounting frame: versions without suffixes (example: **NL4MDXX-V**)

■ Front mounted connectors:

- Convenient fastening with countersunk screw holes: (example: **NL4MPXX**)

Please see the recommended options including the torque limits below:

Chassis connector (note mounting hole type)		Screw Type Part number example (screws not included)		Mounting version & maximum allowable torque M_A	
				Rear assembly	Front assembly
			NL4M*XX-* (no suffix)		
			<ul style="list-style-type: none"> • Countersunk thru holes for countersunk machine screws (e.g.: M3, 4-40) 	90 Ncm	60 Ncm
			NL4M*XX*-2 (-2 suffix)		
			<ul style="list-style-type: none"> • Mirrored self-tapping screw holes for Neutrik A-screw (rear mount only) 	90 Ncm	-
			NL4M*XX*-3 (-3 suffix)		
			<ul style="list-style-type: none"> • Standard orientation self-tapping screw holes for Neutrik A-screw (rear mount only) 	90 Ncm	-

Neutrik AG	LI	T: +423 / 237 24 24	F: +423 / 232 53 93	Neutrik France	FR	T: +33 1 / 4131 6750	F: +33 1 / 4131 0511
Neutrik USA Inc.	USA	T: +1 704 / 972 3050	F: +1 704 / 438 9202	Neutrik Tokyo Ltd.	JP	T: +81 3 / 3663 4733	F: +81 3 / 3663 4796
Neutrik (UK) Ltd.	UK	T: +44 1983 / 811 441	F: +44 1983 / 811 439	Neutrik Hong Kong Ltd.	HK	T: +852 / 2687 6055	F: +852 / 2687 6052
Neutrik Vertriebs GmbH	DE/NL/AT/DK	T: +49 8131 / 280 890	F: +49 8131 / 280 830	Neutrik India Pvt. Ltd.	IND	T: +91 / 982 05 43 424	F: +91 / 22 26163 540

Draft. Nr.: BDA 591 V1 | Update: 2020-05-20 | Data subject to change without prior notice. © 2020 NEUTRIK®, NEUTRIK® are registered trademark of Neutrik AG. ALL RIGHTS RESERVED.