



HS 2

Headset microphone



FEATURES

- Omni-directional with MKE 2 capsule
- Excellent sound suitable for singers and speakers alike
- Easy handling and rugged construction
- Available in beige and black
- 3.5 mm jack or 3-pin connector

DELIVERY INCLUDES

HS 2 BE | HS 2 BK | HS 2 -4 BE | HS 2 -4 BK

- headband
- 1 x frequency cap, short: MZC 2-1
- 1 x frequency cap, long: MZC 2-2
- quick guide
- safety guide

The HS 2 is a neckworn microphone with a very robust steel wire cable for connection to wireless bodypack transmitters. It features the omni-directional MKE 2 capsule and meets the highest demands on sound quality and robustness. The condenser microphone can easily be brought into the optimum position by the interplay of the small capsule and a short gooseneck. The HS 2 is equally suitable for voice and speech transmission.

PRODUCT VARIANTS

Variant	Colour	Connector	Article number
HS 2 BE	beige	3.5 mm jack plug	508882
HS 2 BK	black	3.5 mm jack plug	508883
HS 2-4 BE	beige	3-pin connector	508884
HS 2-4 BK	black	3-pin connector	508885

ACCESSORIES

MZC 2-1	black	Frequency cap, short	Art. no. 572231
MZC 2-1	beige	Frequency cap, short	Art. no. 572232
MZC 2-2	black	Frequency cap, long	Art. no. 572233
MZC 2-2	beige	Frequency cap, long	Art. no. 572234
MZW 02	black	Windshield, foam	Art. no. 578819
MZW 02	beige	Windshield, foam	Art. no. 578845
MZW 2	black	Windshield	Art. no. 543658
MZW 2 G	beige	Windshield	Art. no. 576123



HS 2

Headset microphone

SPECIFICATIONS

Pick-up pattern	omni-directional
Frequency response	20 - 20,000 Hz
Sensitivity in free field	5 mV/ Pa \pm 3 dB
Nominal impedance	1 k Ω
Min. terminating impedance	4.7 k Ω
Equivalent noise level:	
A-weighted	28 dB
CCIR-weighted	41 dB
Max. sound pressure level	140 dB
Power supply	7.5 V
Connector	3-pin connector 3.5 mm jack plug
Cable length	1.6 m
Diameter of microphone	4.8 mm
Weight	
3.5 mm jack	30.1 g
3-Pin	28.9 g

DIMENSIONS

